



LITHIUM PRODUCT SPECIFICATION GUIDE

Part Number	BCI Group Size	Capacity @ 25°C (77°F)		Energy (Wh)	Current Capability		Dimensions inches (mm)			Weight lbs (kg)	Terminal Type	Case Material
		AH	Min @ 25A		Continuous (A)	Peak (A)	Length	Width	Height			

12V - STANDARD

RB5	NA	5	NA	64	5	10	5.9 (151)	2.6 (65)	3.9 (99)	2.0 (0.9)	F2	ABS
RB12	NA	12	NA	128	10	20	5.9 (151)	3.9 (98)	4.0 (101)	3.6 (1.65)	F2	ABS
RB10-PC	NA	10	24	128	50	70	7.1 (181)	3.0 (76)	6.6 (168)	4.4 (2)	M6	ABS
RB10PVC	NA	10	NA	128	10	20	10.3 (262)	1.4 (36)	3.0 (77)	4.0 (1.8)	Wire Leads	PVC
RB20	NA	20	48	256	20	40	7.1 (181)	3.0 (76)	6.7 (169)	5.6 (2.55)	M6	ABS
RB35	U1	35	84	448	35	70	7.7 (195)	5.2 (131)	6.7 (171)	9.9 (4.5)	M8	ABS
RB40	NA	40	96	512	40	80	7.8 (197)	6.5 (166)	6.8 (173)	11.9 (5.4)	M8	ABS
RB52	NA	50	120	640	52	100	7.8 (197)	6.5 (166)	6.8 (173)	13.7 (6.2)	M8	ABS
RB60	24	60	144	768	60	140	10.2 (260)	6.6 (168)	8.2 (210)	15.9 (7.20)	M8	ABS
RB75	24	75	180	960	75	150	10.2 (260)	6.6 (168)	8.2 (210)	23.6 (10.7)	M8	ABS
RB80	27	80	192	1024	80	160	12.0 (305)	6.6 (168)	8.2 (210)	24.9 (11.3)	M8	ABS
RB80-D	DIN	80	192	1024	80	160	13.2 (335)	6.9 (174)	7.5 (191)	24.9 (11.3)	M8	ABS
RB100	31	100	240	1280	100	200	13.0 (329)	6.8 (172)	8.4 (214)	26.4 (11.98)	M8	ABS
RB100-D	DIN	100	240	1280	100	200	13.2 (335)	6.9 (174)	7.5 (191)	30.2 (13.7)	M8	ABS
RB170	NA	170	408	2176	200	250	19.5 (495)	10.6 (268)	7.9 (201.5)	66.1 (30)	M8	STEEL
RB200	8D	200	480	2560	100	200	20.6 (522)	10.5 (267)	8.7 (220)	61.1 (27.7)	M8	ABS
RB300	8D	300	720	3840	100	200	20.6 (522)	10.5 (267)	8.7 (220)	75.8 (34.36)	M8	ABS

24V - STANDARD

RB24V20	U1	20	48	512	30	60	7.7 (195)	5.2 (131)	6.7 (171)	11.9 (5.4)	M8	ABS
RB24V40	24	40	96	1024	30	70	10.2 (260)	6.6 (168)	8.2 (210)	28.7 (13)	M8	ABS
RB24V52	31	52	120	1280	50	100	13.0 (329)	6.8 (172)	8.4 (214)	29.1 (13.2)	M8	ABS
RB24V100	8D	100	240	2560	100	200	20.6 (522)	10.5 (267)	8.7 (220)	61.1 (27.7)	M8	ABS
RB24V200	NA	200	480	5120	200	250	16.1 (410)	13.7 (349)	16.4 (417)	110.2 (50)	M10	STEEL

Part Number	BCI Group Size	Capacity @ 25°C (77°F)		Energy (Wh)	Current Capability		Dimensions inches (mm)			Weight lbs (kg)	Terminal Type	Case Material
		AH	Min @ 25A		Continuous	Peak						
48V - STANDARD												
RB48V25	24	25	300	1280	20	25	10.2 (260)	6.6 (168)	8.2 (210)	27.6 (12.5)	M8	ABS
RB48V100	NA	100	240	5120	200	250	32.8 (832.4)	11.2 (285)	10 (255)	62 (136.7)	M10	STEEL
RB48V200	NA	200	480	10240	200	250	34.3 (867)	14.2 (358)	15.6 (393)	302 (137)	M10	STEEL
RB48V300	NA	300	720	15360	200	250	29.1 (740)	19.6 (497)	15.7 (398)	388 (176)	M10	STEEL

INSIGHT SERIES

24V060-GC2	GC2	60	144	1.536	100	240	10.2 (260)	7.1 (180)	10.9 (276)	34.4 (15.6)	M8	ABS
48V030-GC2	GC2	30	72	1.536	100	200	10.2 (260)	7.1 (180)	10.9 (276)	34.4 (15.6)	M8	ABS

12V - LT-SERIES (LOW TEMPERATURE OPERATION)

RB20-LT	NA	20	48	256	20	40	7.1 (181)	3.0 (76)	6.7 (169)	6.6 (3)	M6	ABS
RB52-LT	NA	52	120	640	50	100	7.8 (197)	6.5 (166)	6.8 (173)	14.1 (6.38)	M8	ABS
RB100-LT	31	100	240	1280	100	200	13.0 (329)	6.8 (172)	8.4 (214)	27.9 (12.64)	M8	ABS
RB300-LT	8D	300	720	3840	100	200	20.6 (522)	10.5 (267)	8.7 (220)	76.1 (34.54)	M8	ABS

12V - X-SERIES (HIGH CONTINUOUS AND PEAK PERFORMANCE)

RB20-X	NA	20	48	256	50	90	7.1 (181)	3.0 (76)	6.7 (169)	5.6 (2.55)	M6	ABS
RB35-X	U1	35	84	448	70	100	7.7 (195)	5.2 (131)	6.7 (171)	11 (4.8)	M8	ABS

12V - HP-SERIES (HIGH PEAK PERFORMANCE)

RB100-HP	31	100	240	1280	100	800	13.0 (329)	6.8 (172)	8.4 (214)	29.8 (13.5)	M8	ABS
RB100-DHP	DIN	100	240	1280	100	800	13.2 (335)	6.9 (174)	7.5 (191)	30.2 (13.7)	M8	ABS
RB300-HP	8D	300	720	3840	100	800	20.6 (522)	10.5 (267)	8.7 (220)	82.7 (37.5)	M8	ABS

12V - GOLF TROLLEY

RBGT-16	NA	16	NA	205	16	25	6.6 (168)	5.0 (127)	2.9 (74)	5 (2.1)	ANDERSON	ABS
RBGT-19	NA	19	NA	243	16	25	7.1 (180)	3.0 (76)	6.5 (165)	6 (2.7)	ANDERSON	ABS
RBGT-22	NA	22	NA	282	16	25	6.6 (168)	5.0 (127)	4.0 (102)	6 (2.9)	ANDERSON	ABS

PORTABLE POWER

GYPSY 20	NA	20	NA	74	NA	NA	7.1 (179.6)	3.7 (93.8)	1.2 (30.6)	1 (0.45)	USB A, C, Micro	ABS & Silicone
OUTLAW 1072S	NA	72	NA	921.6	1000	2000	14.5 (368)	7.9 (200)	10.9 (276)	32 (14.5)	Multi AC/DC	ABS & Steel

